

AMENDMENTS TO THE CLAIMS

1-2. (Canceled).

3. (Currently Amended) A mobile station receiving method on a down channel in a CDMA (Code Division Multiple Access) cellular system in which a base station modulates, by using orthogonal pseudo noise sequences, transmission signals towards a plurality of mobile stations, transmits the modulated signals synchronously, while said mobile stations receive the modulated signals distorted by a plurality of radio channels of which delay times are different, said method comprising:
equalizing and demodulating said modulated signals from said base station, by
using a filter of which frequency characteristics ~~is~~ are inverse with that of said
radio channels, thereby generating an equalized, demodulated output;
in parallel, demodulating independently each of said modulated signals and
combining the demodulation results, thereby generating a conventional output;
and
selecting an output with higher communication quality from the equalized,
demodulated output and the conventional output.

4. (Currently amended) The mobile station receiving method according to claim 3, wherein said equalizing step further comprises:
connecting a plurality of delay circuits in series;
multiplying a prescribed weight coefficient by the output from each delay circuit
using a plurality of multipliers; and
adding the outputs from said multipliers, wherein said modulated signals are
equalized adaptively as the distortions of said radio channels
~~changes~~change.

5. (Canceled).

6. (Currently Amended) A mobile station receiving apparatus on a down channel in a CDMA (Code Division Multiple Access) cellular system in which a base station modulates, by using orthogonal pseudo noise sequences, transmission signals towards a plurality of mobile stations, transmits the modulated signals synchronously, while said mobile stations receive the modulated signals distorted by a plurality of radio channels of which delay times are different, which is characterized in that said mobile station comprises:

a first receiving unit,

a second receiving unit and

a selection unit,

wherein said first receiving unit comprises:

a frequency conversion unit for converting said modulated signals received by an antenna into base band signals;

a channel estimation unit for detecting frequency characteristics of said radio channels on the basis of said modulated signals;

a filter unit having frequency characteristics that are inverse from said radio channels' frequency characteristics; and

a demodulator for demodulating the outputs from said filter unit of which inputs are said base band signals, and

said second receiving unit comprises:

a demodulation unit for demodulating independently each of said modulated signals which pass through a plurality of said radio channels of which delay times are different; and

a combining unit for combining the demodulation results,

which is characterized in that said selection unit selects an output with higher communication quality ~~is selected among the outputs by said first and second receiving units.~~

7. (Canceled).

8. (Currently Amended) A communication system on a down channel in a CDMA (Code Division Multiple Access) cellular system in which a base station modulates, by using orthogonal pseudo noise sequences, transmission signals towards a plurality of mobile stations, transmits the modulated signals synchronously, while said mobile stations receive the modulated signals distorted by a plurality of radio channels of which delay times are different, said mobile stations comprise:

a first receiving unit, comprising:

a frequency conversion unit for converting said modulated signals

received by an antenna into base band signals;

a channel estimation unit for detecting frequency characteristics of said

radio channels on the basis of said modulated signals;

a filter unit having frequency characteristics which are inverse of

frequency characteristics of said radio channels; and

a demodulator for demodulating the outputs from said filter unit of

which inputs are said ~~based~~-base band signals,

a second receiving unit, comprising:

a demodulation unit for demodulating independently each of said

modulated signals that pass through said plurality of radio channels,

where each channel has a different delay time and a combining unit

for combining the demodulation results, and

a selection unit that selects an output of said first and second receiving units that has higher communication quality.

9. (Canceled).
10. (Previously Presented) The mobile station receiving method according to claim 3, wherein said equalizing is performed before said demodulating in said equalizing and demodulating step.